


CHANNEL

SAFETY SYSTEMS

STRATOS ULTRA



**1500Lm
Maintained**

**ULTRA HIGH OUTPUT
Emergency luminaire**

LED





LED Emergency Luminaire

The Stratos Ultra LED bulkhead is ideal for use in area with high ceilings or areas requiring high emergency lux levels- The Stratos Ultra gives 1500 lumen output in the emergency mode!

Mains LM output 320Lm
 Emergency LM output 1500Lm
 Mains Wattage 18w
 Battery Ni-cd 9.6v 4500mAh
 LED 42x SMD 2835

Features

- Approximately **15x** the light output of a typical LED bulkhead.
- Long life LED technology
- Maintained or non-maintained operation
- Polycarbonate construction with clear diffuser
- Hinged gear tray for easy installation
- Cable entry: rear, end & side of fitting
- Easy to install
- Low environmental impact
- Low running costs
- Low maintenance
- Meets BS EN 60598-2-22 and other relevant standards



Stratos Ultra	Mounting Height	Transverse Distance To wall	Transverse Distance between luminaires	Axial Distance to wall	Axial Distance between luminaires
1500Lm 1 lux	3m	8.40	14.30	8.30	14.00
	6m	11.40	20.30	9.20	19.70
	10m	11.30	20.60	11.10	20.10
	15m	12.85	26.10	10.30	25.80
	18m	13.10	31.40	12.60	27.30

SPECIFICATIONS

Light Source	42x LED SMD 2835
IP Rating	IP65
Emergency Duration	3 hours (minimum)
Mains Voltage	230V 50Hz ± 10%
Mains Current (max)	90mA (18W)
Recharge Period	Less than 24 hours
Charge Indicator	Integral green LED
Changeover Voltage	As per the requirements of BS EN 60598-2-22
Temperature Range	-5°C to 40°C
Weight	950g
Battery	9.6V 4.5Ah Nickel Cadmium

PRODUCT CODE	DESCRIPTION
E/STRATOS/ULTRA	Stratos ultra self contained 3 hour maintained emergency LED light



www.channelsafety.co.uk

Tel: 0845 884 7000

Email: sales@channelsafety.co.uk

Errors & omissions excluded. Specification is subject to change without notice.

revision-1