



Attestation of Compliance

Reference No. : LCSB01094038S

Applicant : SHINELONG TECHNOLOGY CORP., LTD.

Address : BLDG A & B, No. 12th DaKeng Rd., TongLe, BaoLong street,
LongGang, ShenZhen, China, 518118

Product : Explosion proof luminaire

Trade Mark : ShineLong

Model(s) : See ANNEX I

Parameters : See ANNEX I

Tested according to : EN IEC 60598-2-1:2021; EN IEC 60598-1:2021+A11:2022;
EN 62493:2015+A1:2022; EN IEC 62031:2020+A11:2021;

The submitted products have been tested by us with the listed standards.

This Attestation of Compliance is issued according to the council Directive 2014/35/EU, Referred to as the Low Voltage Directive. It confirms that the listed product complies with all essential requirements of the LVD Directive and applies only to the sample and its technical documentation submitted to Shenzhen Southern LCS Compliance Testing Laboratory Ltd. for testing.

After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant Directives have to be observed.



Date of issue: January 29, 2024

Manager





ANNEX I:

Reference No. : LCSB01094038S

Model(s) :

Model	Rating
SL-P69X2-20-YD	220-240V~, 50/60Hz, 20W, Class I, ta.40°C, IP66
SL-P69X2-30-YD	220-240V~, 50/60Hz, 30W, Class I, ta.40°C, IP66
SL-P69X3-30-YD	220-240V~, 50/60Hz, 30W, Class I, ta.40°C, IP66
SL-P69X4-36-YD	220-240V~, 50/60Hz, 36W, Class I, ta.40°C, IP66
SL-P69X4-40-YD	220-240V~, 50/60Hz, 40W, Class I, ta.40°C, IP66
SL-P69X4-50-YD	220-240V~, 50/60Hz, 50W, Class I, ta.40°C, IP66
SL-P69X5-45-YD	220-240V~, 50/60Hz, 45W, Class I, ta.40°C, IP66
SL-P69X5-50-YD	220-240V~, 50/60Hz, 50W, Class I, ta.40°C, IP66
SL-P69X5-60-YD	220-240V~, 50/60Hz, 60W, Class I, ta.40°C, IP66
SL-P69X2-20-YDD	220-240V~, 50/60Hz, 20W, Class I, ta.40°C, IP66
SL-P69X2-30-YDD	220-240V~, 50/60Hz, 30W, Class I, ta.40°C, IP66
SL-P69X3-30-YDD	220-240V~, 50/60Hz, 30W, Class I, ta.40°C, IP66
SL-P69X4-36-YDD	220-240V~, 50/60Hz, 36W, Class I, ta.40°C, IP66
SL-P69X4-40-YDD	220-240V~, 50/60Hz, 40W, Class I, ta.40°C, IP66
SL-P69X4-50-YDD	220-240V~, 50/60Hz, 50W, Class I, ta.40°C, IP66
SL-P69X5-45-YDD	220-240V~, 50/60Hz, 45W, Class I, ta.40°C, IP66
SL-P69X5-50-YDD	220-240V~, 50/60Hz, 50W, Class I, ta.40°C, IP66
SL-P69X5-60-YDD	220-240V~, 50/60Hz, 60W, Class I, ta.40°C, IP66

